

Akin 3000

The worthy protector

PN: PWAV-30002AK-AZ01B

EAN: 6422956006198

Specifications

Capacity	3000 VA / 2400 W
Socket type	1 x Schuko, 1 x IEC C19
Input	
Nominal voltage	220 VAC
Accepted voltage range	110 VAC - 270 VAC or 140 VAC - 260 VAC (Selectable)
Frequency range	60 Hz or 50 Hz
Output	
Nominal voltage	230 VAC
Voltage regulation	± 10%
Efficiency	
Normal mode	95%
AVR mode	92%
Protection	
Delay time	3 minutes or 10 Seconds
Full protection	Over-voltage, Under-voltage, Overheat, Over current protection, Surge protection
Indicators	
LED indicator	Normal indicator, AVR indicator, Delay time setting, Fault indicator
Normal mode	Green lighting
Activate voltage range switch mode	Yellow & Green LED lighting
Output adjustable voltage range mode	Red & Green LED lighting
Time delay	Red LED flashing & Green lighting
Digital display	Input and output voltage
Environment	
Humidity	0-90 % (non-condensing)
Temperature	0-40°C



Digital display



Time delay
function



Selectable input
voltage range




- Microprocessor control guarantees high reliability
- Selectable input voltage range
- Time delay function eliminates transients that can effect connected equipment
- Under-voltage, over-voltage, over-heat and over current protection
- Provides stable output voltage
- Provide surge and spike suppression

Physical

Product dimensions	297.1 x 150 x 199 mm
Product weight	8.56 kg



Logistics

 Carton Box Size (LxWxH)	350 x 250 x 295 mm
 Pieces in the Carton Box	1
 Net & Gross weight / CTN	NW: 8.56 kg / GW: 10.2 kg

Certificates

RoHS
2011/65/EU 