

Aira 1200

The faultless defender

PN: UPCSTLP812HAICP01B
EAN: 6422956012632

Specifications

Capacity	1200 VA / 1000 W
Type	Line Interactive
Input	
Nominal Voltage	230 VAC
Accepted Voltage Range	145~275 VAC
Frequency	50Hz
Output	
Nominal Voltage	230 VAC
Accepted Output Voltage Range	213~248Vac
AC Voltage Regulation (Batt. Mode)	±8%
Frequency Range	50 Hz
Waveform (Batt. Mode)	Pure Sine Wave
Transfer Time	<10 ms
Inrush current	3000 W
Indicators type & Alarm	
LCD Display	AC Mode, Battery Mode, Load Level, Battery Level, Input Voltage, Output Voltage, Frequency
Protection	
Outlets type	2 x Schuko Battery Backup
Full protection	Overload, battery discharge and over-charge protection
Operating Environment	
Humidity	20% ~ 90% (non-condensing)
Operating Temperature	0° C to 40° C



10A / 20A



Central heating
unit ready



Long
back-up time

- Selectable charging current (10A or 20A)
- Ideal for central heating units
- Long backup time
- Overload protection
- Short circuit protection
- Cold start function
- Off mode charging
- Automatic Voltage Regulation
- Auto restart while AC is recovering
- Car battery adapter included

Battery


Battery Voltage	12VDC
Charging current	Selectable 10A or 20A
Battery type	Car type battery or Deep-cycle battery (not included)
Recommended battery capacity	From 40Ah to 200Ah

Physical

Product dimensions	255 x 290 x 120 mm
Product weight	11.3 kg
Retail Pack Dimensions	310 x 340 x 207 mm
Retail Pack Weight	12.2 kg



Logistics

 Carton Box Size	355 x 325 x 435 mm
 Pieces in the Carton Box	2 pcs / ctn
 Net & Gross weight / CTN	N.W. / G.W.: 24.4 kg / 25.4 kg



Certificates

